

```
# DIFF
###WARNING: NO CUSTOM DEFAULTS FOUND###
# version
# Betaflight / STM32F405 (S405) 4.3.1 Jul 13 2022 / 03:32:11 (8d4f005) MSP API: 1.44
###ERROR IN diff: NO CONFIG FOUND###
# start the command batch
batch start
board_name FLYWOOF405NANO
manufacturer_id FLWO
# name: FLYWOO
# resources
resource BEEPER 1 C13
resource MOTOR 1 B00
resource MOTOR 2 B01
resource MOTOR 3 A03
resource MOTOR 4 A02
resource MOTOR 5 B05
resource MOTOR 6 C09
resource MOTOR 7 B07
resource MOTOR 8 C08
resource PPM 1 B08
resource LED_STRIP 1 A09
resource SERIAL_TX 1 B06
resource SERIAL_TX 2 D05
resource SERIAL_TX 3 B10
resource SERIAL_TX 4 A00
resource SERIAL_TX 6 C06
resource SERIAL_RX 1 A10
resource SERIAL_RX 2 D06
resource SERIAL_RX 3 B11
resource SERIAL_RX 4 A01
resource SERIAL_RX 5 D02
resource SERIAL_RX 6 C07
resource I2C_SCL 1 B08
resource I2C_SDA 1 B09
resource LED 1 C14
resource SPI_SCK 1 A05
resource SPI_SCK 3 C10
resource SPI_MISO 1 A06
resource SPI_MISO 3 C11
resource SPI_MOSI 1 A07
resource SPI_MOSI 3 C12
resource ESCSERIAL 1 B08
resource ADC_BATT 1 C03
resource ADC_RSSI 1 C00
resource ADC_CURR 1 C02
resource FLASH_CS 1 B03
resource OSD_CS 1 B14
```

resource GYRO_EXTI 1 B13
resource GYRO_CS 1 B12
resource USB_DETECT 1 A08
timer
timer B00 AF2
pin B00: TIM3 CH3 (AF2)
timer B01 AF2
pin B01: TIM3 CH4 (AF2)
timer A03 AF1
pin A03: TIM2 CH4 (AF1)
timer A02 AF1
pin A02: TIM2 CH3 (AF1)
timer B05 AF2
pin B05: TIM3 CH2 (AF2)
timer B07 AF2
pin B07: TIM4 CH2 (AF2)
timer C09 AF3
pin C09: TIM8 CH4 (AF3)
timer C08 AF3
pin C08: TIM8 CH3 (AF3)
timer A09 AF1
pin A09: TIM1 CH2 (AF1)
dma
dma ADC 1 0
ADC 1: DMA2 Stream 0 Channel 0
dma pin B00 0
pin B00: DMA1 Stream 7 Channel 5
dma pin B01 0
pin B01: DMA1 Stream 2 Channel 5
dma pin A03 1
pin A03: DMA1 Stream 6 Channel 3
dma pin A02 0
pin A02: DMA1 Stream 1 Channel 3
dma pin B05 0
pin B05: DMA1 Stream 5 Channel 5
dma pin B07 0
pin B07: DMA1 Stream 3 Channel 2
dma pin C09 0
pin C09: DMA2 Stream 7 Channel 7
dma pin C08 0
pin C08: DMA2 Stream 2 Channel 0
dma pin A09 0
pin A09: DMA2 Stream 6 Channel 0
feature
feature -RX_PARALLEL_PWM
feature RX_SERIAL
feature MOTOR_STOP
feature TELEMETRY

```
feature LED_STRIP
feature OSD
# serial
serial 2 1 115200 57600 0 115200
serial 3 64 115200 57600 0 115200
# mixer
mixer HEX6X
# led
led 0 6,6::CO:8
led 1 7,6::CO:8
led 2 8,6::CO:8
led 3 9,6::CO:8
# aux
aux 0 0 1 1375 2100 0 0
aux 1 2 1 1700 2100 0 0
# vtxtable
vtxtable bands 5
vtxtable channels 8
vtxtable band 1 BAND_A A CUSTOM 5865 5845 5825 5805 5785 5765 5745 5725
vtxtable band 2 BAND_B B CUSTOM 5733 5752 5771 5790 5809 5828 5847 5866
vtxtable band 3 BAND_E E CUSTOM 5705 5685 5665 5645 5885 5905 5925 5945
vtxtable band 4 AIRWAVE F CUSTOM 5740 5760 5780 5800 5820 5840 5860 5880
vtxtable band 5 RACEBAND R CUSTOM 5658 5695 5732 5769 5806 5843 5880 5917
vtxtable powerlevels 5
vtxtable powervalues 25 100 200 400 600
vtxtable powerlabels 25 50 100 200 MAX
# rxfail
rxfail 6 s 2000
# master
set acc_calibration = 5,13,-13,1
set mag_bustype = I2C
set mag_i2c_device = 1
set mag_hardware = NONE
set baro_bustype = I2C
set baro_i2c_device = 1
set serialrx_provider = CRSF
set blackbox_device = SPIFLASH
set dshot_burst = ON
set motor_pwm_protocol = DSHOT300
set current_meter = ADC
set battery_meter = ADC
set ibata_scale = 200
set beeper_inversion = ON
set beeper_od = OFF
set yaw_motors_reversed = ON
set pid_process_denom = 4
set osd_vbat_pos = 2305
set osd_rssi_pos = 2177
```

```
set osd_rssi_dbm_pos = 161
set osd_tim_1_pos = 2401
set osd_tim_2_pos = 2369
set osd_flymode_pos = 2241
set osd_throttle_pos = 2361
set osd_vtx_channel_pos = 2209
set osd_current_pos = 2391
set osd_mah_drawn_pos = 2273
set osd_craft_name_pos = 2081
set osd_gps_speed_pos = 2264
set osd_gps_lon_pos = 2129
set osd_gps_lat_pos = 2097
set osd_gps_sats_pos = 2167
set osd_home_dir_pos = 2190
set osd_home_dist_pos = 2200
set osd_flight_dist_pos = 2232
set osd_altitude_pos = 2327
set osd_warnings_pos = 2441
set osd_avg_cell_voltage_pos = 2337
set osd_disarmed_pos = 2411
set osd_flip_arrow_pos = 2113
set osd_core_temp_pos = 2296
set osd_log_status_pos = 2145
set osd_efficiency_pos = 231
set osd_displayport_device = MSP
set system_hse_mhz = 8
set vtx_band = 3
set vtx_channel = 4
set vtx_power = 5
set vtx_freq = 5645
set max7456_spi_bus = 3
set displayport_msp_serial = 2
set dashboard_i2c_bus = 1
set pinio_box = 40,41,255,255
set flash_spi_bus = 3
set gyro_1_bustype = SPI
set gyro_1_spibus = 1
set gyro_1_sensor_align = CW90
set gyro_1_align_yaw = 900
set gyro_2_spibus = 1
set name = FLYWOO
profile 0
# profile 0
set p_pitch = 66
set i_pitch = 99
set d_pitch = 76
set p_roll = 61
set i_roll = 94
```

```
set d_roll = 70
set f_roll = 119
set p_yaw = 65
set i_yaw = 99
set f_yaw = 119
set d_min_roll = 46
set d_min_pitch = 51
set simplified_pids_mode = OFF
rateprofile 0
# end the command batch
batch end
#
SAVE
```